

The Art of Music Reproduction



3510 CD Player

Outputs

Output Level :	2V RMS
Frequency Response :	20Hz - 20kHz \pm 0.25dB
Total Harmonic Distortion :	<0.007%, 20Hz - 20kHz, 0dBfs
Signal to Noise Ratio :	>100dB, A weighted
Digital Outputs :	SP/DIF, Coaxial and "Toslink" Optical

General

Mains Supply :	110/120V or 220/240V, 50/60Hz (factory set)
Fuse :	T2AL for 110/120V units T1AL for 220/240V units
Power Consumption :	<25W
Dimensions (HxWxD) :	90mm x 440mm x 300mm
Net Weight :	5kg
Gross Weight :	6.5kg

Features

- Dual mono PCM1704 24 bit DAC fitted to provide very high resolution and separation
- CD display can be turned off for improved sound quality
- Highly optimised audio circuitry with discrete output stage and multiple stages of regulation
- Large toroidal power transformer with separate windings for CD transport mechanism and audio stages
- Employment of a high-stability crystal clock reference and dedicated, power supply regulator for the transport and audio stages to ensure low jitter performance
- High quality double-sided PCBs for optimum layout and screening
- High quality all aluminium case work
- Remote control
- Three year guarantee
- Available in black or titanium

